


## Manto Adjustable 550lm 927 36° 8W WH Phasecut IP5

 $\mathbf{\Delta}^{\mathbf{i}}$ 

🖒 68-74mm






CE	IP54	230V 50Hz	

## SPECIFICATIONS

System Power [W]:	8W	
CCT (Color Temperature):	2700К	
CRI / Ra:	90	
Lumen Output:	550lm	
Beam Angle:	36°	
Lens (Diffuser):	Clear	
Dimming:	Phase-Cut	
System Voltage [V]:	230V 50Hz	
Connection:	QuickConnect	
Mounting:	Recessed, Ceiling	
Cut-out [mm]:	Ø68-Ø74mm	
Lifetime [h]:	L80B50: 50 000h	
Lumen/W:	70lm/W	
MacAdam (SDCM):	3	
Color:	White	
Height [mm]:	50mm	
Width [mm]:	80mm	
Weight [kg]:	0,27kg	
To be recessed in insulation:	No	



Manto Downlight has a cut-out Ø67-74mm that makes is perfect for retrofit to replace old halogen downlights with LED. The downlight is dimmable and can be tilted 25°. Driver included.

NORLUX AS | Borgeskogen 32, 3160 Stokke | post@norlux.com | +47 33 30 10 80 | www.norlux.com