




Cone Spotlight





Cone shaped spotlight with high lumen efficiency for use in 3-circuit track. Available in black and white color with 3000K and CRI 90.

SPECIFICATIONS Lightsource Type: LED (built in) System Power [W]: 26W CCT (Color Temperature): 3000K CRI / Ra: 80 Lumen Output: 2776lm Lumen LED (tc=25): 3800lm Beam Angle: 40 Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm Weight [kg]: 0,75kg	CE IP20 P20 P230V A*	
System Power [W]: 26W CCT (Color Temperature): 3000K CRI / Ra: 80 Lumen Output: 2776lm Lumen LED (tc=25): 3800lm Beam Angle: 40 Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	SPECIFICATIONS	
CCT (Color Temperature): 3000K CRI / Ra: 80 Lumen Output: 2776lm Lumen LED (tc=25): 3800lm Beam Angle: 40 Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	Lightsource Type:	LED (built in)
CRI / Ra: 80 Lumen Output: 2776lm Lumen LED (tc=25): 3800lm Beam Angle: 40 Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	System Power [W]:	26W
Lumen Output: 2776lm Lumen LED (tc=25): 3800lm Beam Angle: 40 Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	CCT (Color Temperature):	3000K
Lumen LED (tc=25): 3800lm Beam Angle: 40 Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	CRI / Ra:	80
Beam Angle: Lens (Diffuser): Clear Dimming: None System Voltage [V]: Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]:	Lumen Output:	2776lm
Lens (Diffuser): Dimming: None System Voltage [V]: Connection: Track 3-Circuit Mounting: Lifetime [h]: Lumen/W: Color: Black Height [mm]: 100mm	Lumen LED (tc=25):	3800lm
Dimming: None System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	Beam Angle:	40
System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	Lens (Diffuser):	Clear
Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	Dimming:	None
Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	System Voltage [V]:	230V 50Hz
Lifetime [h]: L80B10: 100 000h Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	Connection:	Track 3-Circuit
Lumen/W: 107lm/W Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	Mounting:	Track, Ceiling
Color: Black Height [mm]: 196,5mm Width [mm]: 100mm	Lifetime [h]:	L80B10: 100 000h
Height [mm]: 196,5mm Width [mm]: 100mm	Lumen/W:	107lm/W
Width [mm]: 100mm	Color:	Black
	Height [mm]:	196,5mm
Weight [kg]: 0,75kg	Width [mm]:	100mm
	Weight [kg]:	0,75kg