


Panel







Panel LED is a light fixture for interior use. It is constructed for fitting in to suspended ceilings. Panel LEDs can be installed as a pendant or mounted on ceiling surfaces. The Panel LED has an opal or micro prismatic diffusor. Choose between ON/OFF, Phase-Cut or DALI2 (CLO, Corridor, Push dim and Ready2mains) driver. See accessories for detailed information.

| SPFC | IFICATIONS | |
|-------|------------|--|
| JF LU | ILICATIONS | |

| System Power [W]:36WCCT (Color Temperature):3000KCRI / Ra:80Lumen Output:4165lmLumen LED (tc=25):4500lmBeam Angle:110°Lens (Diffuser):OpalDimming:Depending on DriverSystem Voltage [V]:230V 50HzConnection:EPN0024Mounting:L80850: 100 000hLifetime [h]:L80850: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:8,6mmWidth [mm]:1195mm | Lightsource Type: | LED (built in) |
|---|--------------------------|---------------------|
| CRI / Ra:80Lumen Output:4165lmLumen LED (tc=25):4500lmBeam Angle:110°Lens (Diffuser):OpalDimming:Depending on DriverSystem Voltage [V]:230V 50HzConnection:EPN0024Mounting:L80B50: 100 000hLifetime [h]:L80B50: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:8,6mmWidth [mm]:1195mm | System Power [W]: | 36W |
| Lumen Output:4165lmLumen LED (tc=25):4500lmBeam Angle:110°Lens (Diffuser):OpalDimming:Depending on DriverSystem Voltage [V]:230V 50HzConnection:EPN0024Mounting:Recessed, CeilingLifetime [h]:L80B50: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | CCT (Color Temperature): | 3000K |
| Lumen LED (tc=25):4500lmBeam Angle:110°Lens (Diffuser):OpalDimming:Depending on DriverSystem Voltage [V]:230V 50HzConnection:EPN0024Mounting:Recessed, CeilingLifetime [h]:L80B50: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | CRI / Ra: | 80 |
| Beam Angle:110°Lens (Diffuser):OpalDimming:Depending on DriverSystem Voltage [V]:230V 50HzConnection:EPN0024Mounting:Recessed, CeilingLifetime [h]:L80B50: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | Lumen Output: | 4165lm |
| Lens (Diffuser):OpalDimming:Depending on DriverSystem Voltage [V]:230V 50HzConnection:EPN0024Mounting:Recessed, CeilingLifetime [h]:L80B50: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | Lumen LED (tc=25): | 4500lm |
| Dimming:Depending on DriverSystem Voltage [V]:230V 50HzConnection:EPN0024Mounting:Recessed, CeilingLifetime [h]:L80B50: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | Beam Angle: | 110° |
| System Voltage [V]:230V 50HzConnection:EPN0024Mounting:Recessed, CeilingLifetime [h]:L80B50: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | Lens (Diffuser): | Opal |
| Connection:EPN0024Mounting:Recessed, CeilingLifetime [h]:L80B50: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | Dimming: | Depending on Driver |
| Mounting:Recessed, CeilingLifetime [h]:L80B50: 100 000hLumen/W:116lm/WColor:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | System Voltage [V]: | 230V 50Hz |
| Lifetime [h]: L80B50: 100 000h Lumen/W: 116lm/W Color: White Length [mm]: 295mm Height [mm]: 8,6mm Width [mm]: 1195mm | Connection: | EPN0024 |
| Lumen/W:116lm/WColor:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | Mounting: | Recessed, Ceiling |
| Color:WhiteLength [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | Lifetime [h]: | L80B50: 100 000h |
| Length [mm]:295mmHeight [mm]:8,6mmWidth [mm]:1195mm | Lumen/W: | 116lm/W |
| Height [mm]: 8,6mm Width [mm]: 1195mm | Color: | White |
| Width [mm]: 1195mm | Length [mm]: | 295mm |
| | Height [mm]: | 8,6mm |
| Weight [kg] 2.6kg | Width [mm]: | 1195mm |
| | Weight [kg]: | 2,6kg |

