




FDV SPEC SHEET

Tigrus Tilttable


Art. no: 24930-36-2



76-83mm



Tigrus Tilttable



A⁺

Art. no: 24930-36-2

LIGHT TECHNICAL

Lumen Output:	530
Lumen LED (tc=25):	550
Beam Angle:	36°
CCT (Color Temperature):	3000
CRI / Ra:	95
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	QuickConnect
Cut-out [mm]:	76-83
Mounting:	Ceiling, Recessed

ELECTRICAL DATA

Dimming:	Phase-Cut
System Power [W]:	7
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Leakage current [mA]:	5
Inrush current I _{max} [A]:	5
Inrush current time [μs]:	300
Socket / Cap-Base:	N/A
Current Output [mA]:	350



FDV SPEC SHEET

Tigrus Tilttable

Art. no: 24930-36-2



PRODUCT

To be recessed in insulation:	Yes, recessed in insulation
Ingress Protection:	IP44
Impact Protection:	IK02
Operating Temperature [°C]:	-20 - 45
Color:	Black
Height [mm]:	45
Width [mm]:	95