FDV SPEC SHEET
Tigrus Square Double 360° Adjustable
Art. no: 27927-D2W-36-3

Tigrus Square Double 360° Adjustable

IP44 | 230V 50Hz | CE

A

Art. no: 27927-D2W-36-3

LIGHT TECHNICAL	
Lumen Output:	1000
Lumen LED (tc=25):	1100
Beam Angle:	36°
CCT (Color Temperature):	3000-1800K D2W
CRI / Ra:	95
Color Code:	930-918
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION	
Connection:	QuickConnect
Cut-out [mm]:	175x76
Mounting:	Ceiling, Recessed

ELECTRICAL DATA	
Dimming:	Phase-Cut
System Power [W]:	16
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Leakage current [mA]:	5
Inrush current Imax [A]:	5
Inrush current time [µs]:	300
Socket / Cap-Base:	N/A
Current Output [mA]:	700

FDV SPEC SHEET

Tigrus Square Double 360° Adjustable
Art. no: 27927-D2W-36-3

PRODUCT	
To be recessed in insulation:	Yes, recessed in insulation
Ingress Protection:	IP44
Impact Protection:	IK02
Operating Temperature [°C]:	-
Color:	White
Length [mm]:	180
Height [mm]:	47
Width [mm]:	95