




## FDV SPEC SHEET

Cast

Art. no: 1007-6-26-2



## Cast



A

Art. no: 1007-6-26-2

### LIGHT TECHNICAL

Lumen Output:	2980
Lumen LED (tc=25):	3950
Beam Angle:	26°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Clear
UGR (<=):	20

### MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Track, Ceiling

### ELECTRICAL DATA

Dimming:	None
System Power [W]:	36W
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	8
Max load pr circuit - B16:	16
Max load pr circuit - C10:	16
Max load pr circuit - C16:	32
Leakage current [mA]:	0,45
Inrush current I <sub>max</sub> [A]:	25
Inrush current time [μs]:	250
Socket / Cap-Base:	N/A
Current Output [mA]:	900
Voltage Forward Min [V]:	29,2
Voltage Forward Max [V]:	41,6



## FDV SPEC SHEET

Cast

Art. no: 1007-6-26-2



### PRODUCT

Ingress Protection:	IP20
Operating Temperature [°C]:	-
Color:	Black
Length [mm]:	165
Height [mm]:	120
Width [mm]:	85
Weight [kg]:	0,92