


NORLUX


Lighting Solutions



Zeta Mini is a small flexible LED downlight replacing the well-known Zebra mini, offering the same great quality and adjustment possibilities. The Zeta mini is supplied with 18i3 cable connector and can be delivered with a variety of connection options. The down light is available in three different colors.

155mm





| Lightsource Type:                                                                | LED (built in)                                                  |
|----------------------------------------------------------------------------------|-----------------------------------------------------------------|
| System Power [W]:                                                                | 27W                                                             |
| CCT (Color Temperature):                                                         | 2700K                                                           |
| CRI / Ra:                                                                        | 80                                                              |
| Lumen Output:                                                                    | 3031lm                                                          |
| Lumen LED (tc=25):                                                               | 4050lm                                                          |
| Beam Angle:                                                                      | 15°                                                             |
| Lens (Diffuser):                                                                 | Clear                                                           |
| Dimming:                                                                         | None                                                            |
| System Voltage [V]:                                                              | 230V 50Hz                                                       |
|                                                                                  |                                                                 |
| Connection:                                                                      | 18i3 Quick connection                                           |
| Connection:<br>Mounting:                                                         | 18i3 Quick connection<br>Ceiling, Recessed                      |
|                                                                                  |                                                                 |
| Mounting:                                                                        | Ceiling, Recessed                                               |
| Mounting:<br>Cut-out [mm]:                                                       | Ceiling, Recessed<br>155mm                                      |
| Mounting:<br>Cut-out [mm]:<br>Lumen/W:                                           | Ceiling, Recessed<br>155mm<br>112lm/W                           |
| Mounting:<br>Cut-out [mm]:<br>Lumen/W:<br>Color:                                 | Ceiling, Recessed<br>155mm<br>112lm/W<br>Grey                   |
| Mounting:<br>Cut-out [mm]:<br>Lumen/W:<br>Color:<br>Length [mm]:                 | Ceiling, Recessed<br>155mm<br>112lm/W<br>Grey<br>165mm          |
| Mounting:<br>Cut-out [mm]:<br>Lumen/W:<br>Color:<br>Length [mm]:<br>Height [mm]: | Ceiling, Recessed<br>155mm<br>112lm/W<br>Grey<br>165mm<br>125mm |

All specifications are nominal values, deviations may occur.

Product specifications are subject to change without notice. Electrical equipment designed to be part of a fixed electrical installation can only be installed by a registered installation company

Norlux AS Borgeskogen 32 3160 Stokke, Norway A\*\* - A