




FDV SPEC SHEET

Ray Maxi

Art. no: 19143-6-30-1



Ray Maxi



Art. no: 19143-6-30-1

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	5066
Lumen LED (tc=25):	5600
Beam Angle:	30°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Ceiling

PRODUCT

Ingress Protection:	IP20
Operating Temperature [°C]:	-
Color:	Grey
Height [mm]:	281
Width [mm]:	120

ELECTRICAL DATA

Dimming:	None
System Power [W]:	40
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	8
Max load pr circuit - B16:	16
Max load pr circuit - C10:	16
Max load pr circuit - C16:	32
Leakage current [mA]:	0,45
Inrush current I _{max} [A]:	25
Inrush current time [µs]:	250
Socket / Cap-Base:	N/A
Current Output [mA]:	1000
Voltage Forward Min [V]:	30,2
Voltage Forward Max [V]:	41,7