





FDV SPEC SHEET


Torres Mini
Art. no: MA 15016.30.36.35



125mm



Torres Mini



Art. no: MA 15016.30.36.35

LIGHT TECHNICAL

| | |
|-------------------|-------------------|
| Lightsource Type: | LED (replaceable) |
| Beam Angle: | 36° |
| Lens (Diffuser): | Clear |

MOUNTING / CONNECTION

| | |
|---------------|-----------------------|
| Connection: | 18i3 Quick connection |
| Cut-out [mm]: | 125 |
| Mounting: | Ceiling, Recessed |

PRODUCT

| | |
|-------------------------------|-------|
| To be recessed in insulation: | No |
| Ingress Protection: | IP20 |
| Operating Temperature [°C]: | - |
| Color: | Black |
| Length [mm]: | 138 |
| Height [mm]: | 86 |
| Width [mm]: | 94 |

ELECTRICAL DATA

| | |
|--------------------------------------|-----------|
| Dimming: | None |
| System Power [W]: | 35 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 2 |
| Max load pr circuit - B10: | 55 |
| Max load pr circuit - B16: | 90 |
| Max load pr circuit - C10: | 65 |
| Max load pr circuit - C16: | 100 |
| Inrush current I _{max} [A]: | 8 |
| Inrush current time [μs]: | 100 |
| Socket / Cap-Base: | G8 |
| Current Output [mA]: | 600 |