




FDV SPEC SHEET

Lobus BI

Art. no: 7010-7-30-2



Lobus BI



Art. no: 7010-7-30-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	4394
Lumen LED (tc=25):	4750
Beam Angle:	30°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Track, Ceiling

ELECTRICAL DATA

Dimming:	None
System Power [W]:	30
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	30
Max load pr circuit - B16:	50
Max load pr circuit - C10:	50
Max load pr circuit - C16:	85
Inrush current I _{max} [A]:	5
Inrush current time [μs]:	50
Socket / Cap-Base:	N/A
Voltage Forward Min [V]:	29,6
Voltage Forward Max [V]:	39,5



FDV SPEC SHEET

Lobus BI

Art. no: 7010-7-30-2



PRODUCT	
Ingress Protection:	IP20
Operating Temperature [°C]:	-
Lifetime [h]:	L80B10: 50.000
Color:	Black
Length [mm]:	228
Height [mm]:	180
Width [mm]:	97
Weight [kg]:	1,1