




## FDV SPEC SHEET

Lobus BI

Art. no: 7012-7-40-3-ddd



# Lobus BI



Art. no: 7012-7-40-3-ddd

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	3888
Lumen LED (tc=25):	4050
Beam Angle:	40°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

### MOUNTING / CONNECTION

Connection:	Track 3-Circuit+dim
Mounting:	Track, Ceiling

### ELECTRICAL DATA

Dimming:	DALI2
System Power [W]:	30
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B16:	50
Max load pr circuit - C10:	52
Max load pr circuit - C16:	85
Socket / Cap-Base:	N/A
Voltage Forward Min [V]:	29,3
Voltage Forward Max [V]:	38,7



**FDV SPEC SHEET**  
Lobus BI  
Art. no: 7012-7-40-3-ddd



PRODUCT	
Ingress Protection:	IP20
Operating Temperature [°C]:	-
Lifetime [h]:	L80B10: 50.000
Color:	White
Length [mm]:	260
Height [mm]:	180
Width [mm]:	97
Weight [kg]:	1,1