





FDV SPEC SHEET
Z line
Art. no: 102088-01-1-ddd



Z line



Art. no: 102088-01-1-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	13515
Lumen LED (tc=25):	14200
Beam Angle:	90°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3
Lens (Diffuser):	Lens

ELECTRICAL DATA

Dimming:	DALI2
Flickerfree:	Yes
System Power [W]:	74
System Voltage [V]:	230V 50Hz
Protection Class:	1
Current Output [mA]:	500

MOUNTING / CONNECTION

Connection:	QuickConnect
Through-wiring (mm2):	5x2,5
Mounting:	Surface, Ceiling



FDV SPEC SHEET

Z line

Art. no: 102088-01-1-ddd



Lighting Solutions

PRODUCT

Ingress Protection:	IP23
Impact Protection:	IK02
Operating Temperature [°C]:	0 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Steel
Length [mm]:	1700
Height [mm]:	69
Width [mm]:	86
Weight [kg]:	4
Housing Material :	Steel