



FDV SPEC SHEET

Zoom Mini Spotlight

Art. no: 7063-02-560-2-ddd



Lighting Solutions



Zoom Mini Spotlight



Art. no: 7063-02-560-2-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen LED (tc=25):	1250
Beam Angle:	5°-60°
CCT (Color Temperature):	2700
CRI / Ra:	90
Color Code:	927
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Track, Ceiling

PRODUCT

Ingress Protection:	IP20
Lifetime [h]:	L80B50: 50 000
Color:	Black
Length [mm]:	261
Width [mm]:	60
Weight [kg]:	0,95

ELECTRICAL DATA

Dimming:	DALI2
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	15
System Voltage [V]:	230V 50Hz
Dimming Output Type:	Amplitude Modulation
Protection Class:	1
Max load pr circuit - B10:	25
Max load pr circuit - B16:	40
Max load pr circuit - C10:	37
Max load pr circuit - C16:	60
Leakage current [mA]:	0,7
Inrush current I _{max} [A]:	30
Inrush current time [μs]:	100
Current Output [mA]:	500
Voltage Forward Min [V]:	34,2
Voltage Forward Max [V]:	37,7
Dimming Output Type:	Amplitude Modulation