



## **Bladeline Z**





## SPECIFICATIONS

	Lightsource Type:	LED (built in)	
	System Power [W]:	75W	
	CCT (Color Temperature):	3000K	
	CRI / Ra:	80	
	Lumen Output:	12411lm	
	Lumen LED (tc=25):	13000lm	
	Beam Angle:	Wide	
	Dimming:	DALI2	
	System Voltage [V]:	230V 50Hz	
	Connection:	QuickConnect	
	Mounting:	Surface, Ceiling	
	Lifetime [h]:	L80B50: 100 000h	
	Lumen/W:	165lm/W	
	UGR (<=):	21	
	MacAdam (SDCM):	3	
	Through-wiring (mm2):	5x2,5	
	Color:	Aluminium	
	Length [mm]:	1539mm	
	Height [mm]:	70mm	
	Width [mm]:	90mm	
	Weight [kg]:	4kg	



₽4 \$\_\_\_\_\_

5

22

- CE - CE - CE - CE - CE - CE - CE - CE	R			
	150°	180*	150°	
120° 90° 60°		200		120" 90" 60"
	30°	0°	30"	- C90/C270

Bladeline Z is a highly efficient LED luminare with up to 179lm/w. Due to fact that it may be installed surface mounted on the ceiling or on electrical tracks makes it highly flexible. Can be opened without using tools and it has the electric connectors on quick fit clamps. The Bladeline Z is made from galvanized steel with medium or wide beam (75° and 90°) optic in 42W or 75W versions.

cd / 1000 lm