



## PRODUCT SHEET


Bladeline Z

Art. no: 101136-00-1-ddd

# NORLUX®


Lighting Solutions

# Bladeline Z



### SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	42W
CCT (Color Temperature):	4000K
CRI / Ra:	80
Lumen Output:	7554lm
Lumen LED (tc=25):	7800lm
Beam Angle:	Medium
Dimming:	DALI2
System Voltage [V]:	230V 50Hz
Connection:	QuickConnect
Mounting:	Surface, Ceiling
Lifetime [h]:	L80B50: 100 000h
Lumen/W:	179lm/W
UGR (<=):	18
MacAdam (SDCM):	3
Through-wiring (mm2):	5x2,5
Color:	Aluminium
Length [mm]:	1245mm
Height [mm]:	70mm
Width [mm]:	90mm
Weight [kg]:	3,4kg



Bladeline Z is a highly efficient LED luminaire with up to 179lm/w. Due to fact that it may be installed surface mounted on the ceiling or on electrical tracks makes it highly flexible. Can be opened without using tools and it has the electric connectors on quick fit clamps. The Bladeline Z is made from galvanized steel with medium or wide beam (75° and 90°) optic in 42W or 75W versions.