



FDV SPEC SHEET

Arke Bollard

Art. no: 101150-01-20-500-1



Lighting Solutions



Arke Bollard



Art. no: 101150-01-20-500-1

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1669
Lumen LED (tc=25):	1800
CCT (Color Temperature):	3000
CRI / Ra:	80
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Bollard

ELECTRICAL DATA

Dimming:	None
System Power [W]:	20
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	11
Max load pr circuit - B16:	18
Max load pr circuit - C10:	19
Max load pr circuit - C16:	31
Leakage current [mA]:	0,75
Inrush current I _{max} [A]:	53,6
Inrush current time [µs]:	157



FDV SPEC SHEET

Arke Bollard

Art. no: 101150-01-20-500-1



Lighting Solutions

PRODUCT

Ingress Protection:	IP66
Impact Protection:	IK10
Corrosion Class:	C3
Wind force (EPA) [m2]:	0,099
Surge Protection:	L/N-PE = 2KV, L-N = 2KV
Operating Temperature [°C]:	-30 - 50
Lifetime [h]:	L80B10: 100 000
Color:	Grey
RAL:	RAL7022
Height [mm]:	500
Width [mm]:	165
Weight [kg]:	5,5
Housing Material :	Aluminium