



## FDV SPEC SHEET

Arke Bollard

Art. no: 101155-01-20-900-1



*Lighting Solutions*



# Arke Bollard



Art. no: 101155-01-20-900-1

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1754
Lumen LED (tc=25):	1900
CCT (Color Temperature):	4000
CRI / Ra:	80
Lens (Diffuser):	Clear

### MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Bollard

### ELECTRICAL DATA

Dimming:	None
System Power [W]:	20
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	11
Max load pr circuit - B16:	18
Max load pr circuit - C10:	19
Max load pr circuit - C16:	31
Leakage current [mA]:	0,75
Inrush current I <sub>max</sub> [A]:	53,6
Inrush current time [µs]:	157



## FDV SPEC SHEET

Arke Bollard

Art. no: 101155-01-20-900-1



*Lighting Solutions*

### PRODUCT

Ingress Protection:	IP66
Impact Protection:	IK10
Corrosion Class:	C3
Wind force (EPA) [m2]:	0,178
Surge Protection:	L/N-PE = 2KV, L-N = 2KV
Operating Temperature [°C]:	-30 - 50
Lifetime [h]:	L80B10: 100 000
Color:	Grey
RAL:	RAL7022
Height [mm]:	900
Width [mm]:	165
Weight [kg]:	7
Housing Material :	Aluminium