



FDV SPEC SHEET

Panel Round

Art. no: 101271-01-3



Lighting Solutions



Panel Round



Art. no: 101271-01-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	3421
Lumen LED (tc=25):	3500
Beam Angle:	90°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Opal

MOUNTING / CONNECTION

Connection:	Depending on driver
Cut-out [mm]:	360
Mounting:	Recessed, Ceiling

ELECTRICAL DATA

Dimming:	Depending on Driver
System Power [W]:	35
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	14
Max load pr circuit - B16:	23
Max load pr circuit - C10:	23
Max load pr circuit - C16:	38
Leakage current [mA]:	0,16
Inrush current I _{max} [A]:	23
Inrush current time [μs]:	200
Current Output [mA]:	900
Voltage Forward Min [V]:	33
Voltage Forward Max [V]:	38



FDV SPEC SHEET

Panel Round

Art. no: 101271-01-3



Lighting Solutions

PRODUCT

Ingress Protection:	IP20
Operating Temperature [°C]:	-10 - 40
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Height [mm]:	30
Width [mm]:	400
Weight [kg]:	1,62