



FDV SPEC SHEET

Kronos 2800lm Asymmetrical 840 15,9W WH DALI
Art. no: 101630-3-ddd



Kronos 2800lm Asymmetrical 840 15,9W WH DALI



Art. no: 101630-3-ddd

LIGHT TECHNICAL

Lumen LED (tc=25):	2800
Beam Angle:	70°40°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3

MOUNTING / CONNECTION

Connection:	Terminal
Mounting:	Suspended, Wall

PRODUCT

Ingress Protection:	IP40
Impact Protection:	IK05
Operating Temperature [°C]:	0 - 35
Color:	White
Length [mm]:	1140
Height [mm]:	68
Width [mm]:	60
Weight [kg]:	2

ELECTRICAL DATA

Dimming:	DALI
Dimming Output Type:	Amplitude Modulation
Flicker metric (Pst LM) <:	0,02
Stroboscopic effect metric (SVM) <:	0,01
System Power [W]:	15,9
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	20
Max load pr circuit - B16:	33
Max load pr circuit - C10:	34
Max load pr circuit - C16:	56
Inrush current I _{max} [A]:	25
Inrush current time [µs]:	177
Socket / Cap-Base:	N/A
Voltage Forward Min [V]:	54,4
Voltage Forward Max [V]:	55,6