




## FDV SPEC SHEET

Duna

Art. no: 10184745



Lighting Solutions



## Duna



Art. no: 10184745

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	5600
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3
Lens (Diffuser):	PC Opal

### ELECTRICAL DATA

Dimming:	Sensor (MW)
System Power [W]:	46
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	15
Max load pr circuit - B16:	24
Max load pr circuit - C10:	25
Max load pr circuit - C16:	40
Inrush current I <sub>max</sub> [A]:	36
Inrush current time [μs]:	150

### MOUNTING / CONNECTION

Connection:	Terminal
Through-wiring (mm <sup>2</sup> ):	5x2,5
Mounting:	Surface, Wall, Ceiling



## FDV SPEC SHEET

Duna

Art. no: 10184745



*Lighting Solutions*

### PRODUCT

Ingress Protection:	IP66
Impact Protection:	IK08
Operating Temperature [°C]:	-25 - 35
Lifetime [h]:	50 000
Color:	Grey
RAL:	RAL7035
Length [mm]:	1573
Height [mm]:	101
Width [mm]:	84
Weight [kg]:	2,2
Housing Material :	Polycarbonate