




## FDV SPEC SHEET

C Line Base

Art. no: 102516-01-1



Lighting Solutions



## C Line Base



Art. no: 102516-01-1

### LIGHT TECHNICAL

Lightsource Type:	LED (replaceable)
Lumen Output:	10793
Lumen LED (tc=25):	12100
Beam Angle:	90°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

### PRODUCT

Ingress Protection:	IP23
Impact Protection:	IK08
Lifetime [h]:	L80: 100 000
Color:	Steel
Length [mm]:	1250
Height [mm]:	50
Width [mm]:	76
Weight [kg]:	2,04

### ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
Flicker metric (Pst LM) <:	0,028
Stroboscopic effect metric (SVM) <:	0,004
System Power [W]:	60/50/42/33
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	11
Max load pr circuit - B16:	18
Max load pr circuit - C10:	18
Max load pr circuit - C16:	29
Inrush current I <sub>max</sub> [A]:	23
Inrush current time [µs]:	242
Current Output [mA]:	70

### MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Surface, Ceiling