




FDV SPEC SHEET


Torres Mini

Art. no: 17030-7-40-3-ddd




Lighting Solutions

 125mm



Torres Mini



Art. no: 17030-7-40-3-ddd

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 2780 |
| Lumen LED (tc=25): | 3650 |
| Beam Angle: | 40° |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 80 |
| Color Code: | 830 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Clear |

MOUNTING / CONNECTION

| | |
|---------------|----------------------------|
| Connection: | 18i5 DALI Quick connection |
| Cut-out [mm]: | Ø125 |
| Mounting: | Recessed, Ceiling |

ELECTRICAL DATA

| | |
|--------------------------------------|-----------|
| Dimming: | DALI |
| System Power [W]: | 22 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 2 |
| Max load pr circuit - B10: | 55 |
| Max load pr circuit - B16: | 90 |
| Max load pr circuit - C10: | 65 |
| Max load pr circuit - C16: | 100 |
| Inrush current I _{max} [A]: | 8 |
| Inrush current time [µs]: | 100 |
| Socket / Cap-Base: | N/A |
| Current Output [mA]: | 600 |
| Voltage Forward Min [V]: | 29,6 |
| Voltage Forward Max [V]: | 39,5 |



FDV SPEC SHEET

Torres Mini

Art. no: 17030-7-40-3-ddd



Lighting Solutions

PRODUCT

| | |
|-------------------------------|-------|
| To be recessed in insulation: | No |
| Ingress Protection: | IP20 |
| Color: | White |
| Length [mm]: | 138 |
| Height [mm]: | 86 |
| Width [mm]: | 94 |