




Trimo Micro










C € D IP20 SOHE		A** -
SPECIFICATIONS		
Lightsource Type:	LED (built in)	
System Power [W]:	13W	
CCT (Color Temperature):	3000K	
CRI / Ra:	80	
Lumen Output:	1240lm	
Lumen LED (tc=25):	2150lm	
Beam Angle:	40°	
. /- 166		

SPECIFICATIONS	
Lightsource Type:	LED (built in)
System Power [W]:	13W
CCT (Color Temperature):	3000K
CRI / Ra:	80
Lumen Output:	1240lm
Lumen LED (tc=25):	2150lm
Beam Angle:	40°
Lens (Diffuser):	Clear
Dimming:	None
System Voltage [V]:	230V 50Hz
Connection:	18i3 Quick connection
Mounting:	Recessed, Ceiling
Cut-out [mm]:	Ø90mm
Lifetime [h]:	L80B10: 50.000h
Lumen/W:	88lm/W
MacAdam (SDCM):	3
Color:	White
Height [mm]:	140mm
Width [mm]:	95mm
Weight [kg]:	0,65kg
To be recessed in insulation:	No



Tired of downlights giving obtrusive light? This particular model requires a hole dimension of only 90mm. This makes it very versatile with a minimum of stray light, this is accomplished by using a recessed LED light source. The Trimo Micro has a 18i3 connector and can be supplied with a variety of connector solutions.