



PRODUCT SHEET

Driver 350-1050mA cc LCA 75W 350-1050mA one4all lp PRE DALI

Art. no: 28000659



Lighting Solutions

Driver 350-1050mA cc LCA 75W 350-1050mA one4all l

Forward voltage is dependent of current setting. See manufacture datasheet for complete details.



SPECIFICATIONS

System Power [W]:	75W
Dimming:	Corridor, DALI2, Push, Ready2Mains
CC or CV:	CC
CC [mA]:	350 - 1050mA
CC (forward voltage driver) [V]:	40 - 110V
Max output voltage [V]:	250
Output Current Tolerance [%]:	3%
Current Ripple [%]:	2,5%
Current setting:	DALI-2, I-Select 2 Plug (Tridonic), Ready2Ma
Expected Lifetime:	100000h
System Voltage [V]:	230V 50Hz / 176-275VDCV
Protection Class:	1 or 2
Max load pr circuit - B10:	9
Max load pr circuit - B16:	14
Max load pr circuit - C10:	15
Max load pr circuit - C16:	23
Leakage current [mA]:	0,65mA
Inrush current I _{max} [A]:	40A
Inrush current time [μs]:	178μs
Manufacture:	Tridonic
Manufacture P/N:	28000659- Driver 350-1050mA cc LCA 75W 3
Length:	360mm
Height:	21mm
Width:	30mm
Weight:	0,3kg
Operating Temperature [°C]:	-25 - 50