


## **T-Line**







T-Line is our new luminaire for mounting directly into 3-phase track. By using DIP-switch on the wattage setting, you can adjust power to optimize your wattage setting. Choose between 35/40/45W. Preset is set at 50W. T-line comes in 3000K or 4000K with 90°, 120° or double asymmetric beam.



## SPECIFICATIONS

| Lightsource Type:        | LED (built in)   |
|--------------------------|------------------|
| System Power [W]:        | 14-20W           |
| CCT (Color Temperature): | 3000K            |
| CRI / Ra:                | 90               |
| Lumen LED (tc=25):       | 3250lm           |
| Beam Angle:              | 90°              |
| Lens (Diffuser):         | Lens             |
| Dimming:                 | None             |
| System Voltage [V]:      | 230V 50Hz        |
| Connection:              | Track 3-Circuit  |
| Mounting:                | Track            |
| Lifetime [h]:            | L80B10: 100 000h |
| MacAdam (SDCM):          | 3                |
| Color:                   | White            |
| Length [mm]:             | 600mm            |
| Height [mm]:             | 11mm             |
| Width [mm]:              | 61,4mm           |
| Weight [kg]:             | 0,61kg           |
|                          |                  |

 $\mathbf{\Delta}^{\mathsf{H}}$