




FDV SPEC SHEET

Galactic C
Art. no: 9055-02-2



Lighting Solutions



Galactic C



Art. no: 9055-02-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen LED (tc=25):	4200
Beam Angle:	120°
CCT (Color Temperature):	2700-3000K
CRI / Ra:	80
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.

MOUNTING / CONNECTION

Connection:	QuickConnect
Cut-out [mm]:	Ø220-Ø250
Mounting:	Partial-recessed, Surface, Pendant

ELECTRICAL DATA

Dimming:	None
Dimming Output Type:	Amplitude Modulation
System Power [W]:	40
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	12
Max load pr circuit - B16:	20
Max load pr circuit - C10:	20
Max load pr circuit - C16:	34
Leakage current [mA]:	0,5
Inrush current I _{max} [A]:	30
Inrush current time [µs]:	200
Socket / Cap-Base:	N/A
Current Output [mA]:	900



FDV SPEC SHEET

Galactic C

Art. no: 9055-02-2



Lighting Solutions

PRODUCT

Ingress Protection:	IP40
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL9005
Height [mm]:	86
Width [mm]:	400
Weight [kg]:	3,2
Housing Material :	Aluminium