



FDV SPEC SHEET

Galactic C

Art. no: 9057-TW-02-3-ddd



Galactic C



Art. no: 9057-TW-02-3-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen LED (tc=25):	4200
Beam Angle:	120°
CCT (Color Temperature):	2700-6500K
CRI / Ra:	80
Color Code:	827-865
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Partial-recessed, Surface, Pendant

ELECTRICAL DATA

Dimming:	DALI2
Dimming Output Type:	Amplitude Modulation
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
System Power [W]:	40
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	14
Max load pr circuit - B16:	23
Inrush current I _{max} [A]:	27
Inrush current time [µs]:	205
Socket / Cap-Base:	N/A



FDV SPEC SHEET

Galactic C

Art. no: 9057-TW-02-3-ddd



Lighting Solutions

PRODUCT

Ingress Protection:	IP40
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Height [mm]:	86
Width [mm]:	400
Housing Material :	Aluminium