



PRODUCT SHEET

Driver 700mA cc 15W (10-21V) Phasecut JB&SM

Art. no: AS-15-700TF-02



Lighting Solutions

Driver 700mA cc 15W (10-21V) Phasecut JB&SM



SPECIFICATIONS

| | |
|--------------------------------------|--|
| System Power [W]: | 15W |
| Dimming: | Phase-Cut |
| CC or CV: | CC |
| CC [mA]: | 700 - mA |
| CC (forward voltage driver) [V]: | 10 - 21V |
| Max output voltage [V]: | 29 |
| Output Current Tolerance [%]: | 5% |
| Current Ripple [%]: | 20% |
| Current setting: | None |
| Expected Lifetime: | 50000h |
| System Voltage [V]: | 230V 50Hz V |
| Protection Class: | 2 |
| Dimming Minimum Level : | 1% |
| Dimming Phasecut Type: | Leading / Trailing edge |
| Max load pr circuit - B10: | 140 |
| Max load pr circuit - B16: | 224 |
| Max load pr circuit - C10: | 280 |
| Max load pr circuit - C16: | 448 |
| Inrush current I _{max} [A]: | 5A |
| Inrush current time [μs]: | 100μs |
| Manufacture: | AcTEC |
| Manufacture P/N: | AS-15-700TF - Driver 700mA cc 15W (10-21V) |
| Primary Connection: | Quickconnect |
| Secondary Connection: | SM Connector |
| Length: | 85mm |
| Height: | 22mm |
| Width: | 40,4mm |



PRODUCT SHEET

Driver 700mA cc 15W (10-21V) Phasecut JB&SM
Art. no: AS-15-700TF-02



Lighting Solutions

| | |
|---------|--------|
| Weight: | 0,05kg |
|---------|--------|