




Trunk



NORLUX Lighting Solutions



Unit: mm



Trunk is a premium quality and highly advanced linear pendant light system offering

continuous light distribution. We offer a variety of accessories securing easy installation

and various layouts ensuring a natural like lighting to any area. The Trunk light fixtures

are manufactured in ultra-thin steel plates securing a long-life product. The Trunk fixtures

are delivered with all needed installation details in one box and no tools are needed for

the installation. Please see technical table below for detailed information. Batteries for emergency: 1 year warranty

Lightsource Type:
System Power [W]:
CCT (Color Temperature):
CRI / Ra:
Lumen Output:
Lumen LED (tc=25):
Beam Angle:
Lens (Diffuser):

SPECIFICATIONS

System Power [W]:	35W
CCT (Color Temperature):	3000K
CRI / Ra:	80
Lumen Output:	5259lm
Lumen LED (tc=25):	5600lm
Beam Angle:	Right Asymetric
Lens (Diffuser):	Clear
Dimming:	None
System Voltage [V]:	230V 50Hz
Connection:	Trunk 8-wires
Mounting:	Suspended, Ceiling
Lifetime [h]:	L80B50: 100 000h
Lumen/W:	150lm/W
Color:	White
Length [mm]:	1500mm
Height [mm]:	78,6mm
Width [mm]:	72,3mm
Weight [kg]:	1,64kg

LED (built in)

A**