



LED-Strips COB 8,2W/m



The LED Strip COB Short Cut offers perfect, uniform, and comfortable light without visible points or spots, creating an atmosphere that is both inviting and functional. Short distances between each cutting point, with only 13.9 mm per cutting length, provide flexible installation, allowing you to customize the lighting according to your needs and preferences. With 3-step MacAdam color consistency, you can be confident that our light remains stable and uniform over time. Choose between 2700K, 3000K, or 4000K color temperatures. This LED strip has a beam angle of 120° and a CRI of 90, accurately rendering colors in a natural way. Choose between variants with IP20 or IP65 ratings for both indoor and outdoor use.



SPECIFICATIONS CCT (Color Temperature): 4000K CRI / Ra: 90 Color Code: 940 Lumen Output [lm/ m]: 740lm/m Efficiacy [lm/ W]: 90lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 504 System Voltage [V]: 24VDC System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm		
CRI / Ra: 90 Color Code: 940 Lumen Output [lm/ m]: 740lm/m Efficiacy [lm / W]: 90lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 504 System Voltage [V]: 24VDC System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	SPECIFICATIONS	
Color Code: 940 Lumen Output [lm/ m]: 740lm/m Efficiacy [lm/ W]: 90lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 504 System Voltage [V]: 24VDC System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	CCT (Color Temperature):	4000K
Lumen Output [lm/ m]: 740lm/m Efficiacy [lm/ W]: 90lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 504 System Voltage [V]: 24VDC System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	CRI / Ra:	90
Efficiacy [lm/ W]: 90lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 504 System Voltage [V]: 24VDC System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	Color Code:	940
MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 504 System Voltage [V]: 24VDC System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	Lumen Output [lm/ m]:	740lm/m
Beam Angle: 120° LED pr. meter: 504 System Voltage [V]: 24VDC System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	Efficiacy [lm/W]:	90lm/w
LED pr. meter: 504 System Voltage [V]: 24VDC System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	MacAdam (SDCM):	3
System Voltage [V]: 24VDC System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	Beam Angle:	120°
System Power [W/m]: 8,2 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	LED pr. meter:	504
Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: Ingress Protection: Lifetime [h]: L80B10: 50.000h	System Voltage [V]:	24VDC
Heat sink needed: Connection: Cuttable [mm]: Max. length [m]: Ingress Protection: Lifetime [h]: No Cable 2m 13.89mm 5m IP65 L80B10: 50.000h	System Power [W/m]:	8,2
Connection: Cable 2m Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	Dimming:	Depending on Driver
Cuttable [mm]: 13.89mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	Heat sink needed:	No
Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	Connection:	Cable 2m
Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h	Cuttable [mm]:	13.89mm
Lifetime [h]: L80B10: 50.000h	Max. length [m]:	5m
	Ingress Protection:	IP65
Length: 5020mm	Lifetime [h]:	L80B10: 50.000h
	Length:	5020mm
Width: 10mm	Width:	10mm
Weight: 0,176mm	Weight:	0,176mm
Max width Led Strip : 10mm	Max width Led Strip:	10mm