



PRODUCT FAMILY SHEET

Trimo



Lighting Solutions



Trimo

Tired of downlights giving obtrusive annoying stray light? Our Trimo range of downlights guarantees a minimum of stray light, this is accomplished by using a recessed LED light source. The Trimo range has a 18i3 connector and can be supplied with a variety of connector solutions.

VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
18045-7-60-3- ddd	31	4750	3580	3000	60°	Clear	80	White	DALI	5 DALI Quick connect
18045-7-60-2	31	4750	3580	3000	60°	Clear	80	Black	None	18i3 Quick connectio
18045-7-30-3	31	4750	3820	3000	30°	Clear	80	White	None	18i3 Quick connectio
18045-7-20-2	31	4750	3750	3000	20°	Clear	80	Black	None	18i3 Quick connectio
18045-7-60-3	31	4750	3580	3000	60°	Clear	80	White	None	18i3 Quick connectio
18045-7-20-3	31	4750	3750	3000	20°	Clear	80	White	None	18i3 Quick connectio
18045-7-30-2	31	4750	3820	3000	30°	Clear	80	Black	None	18i3 Quick connectio