



PRODUCT SHEET

Driver 24V cv 100W 1-4ch. DALI DT6 SR (TW/RGB/RGBW)

Art. no: W7101



Lighting Solutions

Driver 24V cv 100W 1-4ch. DALI DT6 SR (TW/RGB/RGBW)

Independent digital dimmable LED-driver for constant voltage 24 VDC Supports DALI-2 specification (IEC 62386-207:2018) Select between 1-4 addressable DALI channels DALI-address can easily be set with integrated display (no programming needed) Optimal for Tunable White, RGB and RGBW applications High resolution dimming range 0.1 100 % Max. output power 100 W (24 VDC)



IP20

SPECIFICATIONS	
System Power [W]:	100W
Dimming:	DALI, DALI2
Output Hz:	500
CC or CV:	CV
CV (driver) [V]:	24V
Current Ripple [%]:	3%
Expected Lifetime:	50000h
Protection Class:	2
Dimming Minimum Level :	0,1%
Dimming output type:	PWM
Max load pr circuit - C10:	16
Max load pr circuit - C16:	26
Inrush current I _{max} [A]:	80A
Manufacture:	Wellight
Color:	White
Length:	244mm
Height:	64mm
Width:	32mm
Weight:	0,44kg
Operating Temperature [°C]:	-2 - 45