




Zoom Spotlight





The unique zoom patent makes it possible to vary the beam angel between 6 and 60 degrees making this model highly versatile. The Zoom is available in both black and white versions and is made from robust die-cast aluminum.



Lightsource Type:LED (built in)System Power [W]:20WCCT (Color Temperature):3000KCRI / Ra:90Lumen LED (tc=25):1850ImBeam Angle:6-60Lens (Diffuser):ClearDimming:Phase-CutFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:LasoB10: 100 000hMacAdam (SDCM):3
CCT (Color Temperature):3000KCRI / Ra:90Lumen LED (tc=25):1850ImBeam Angle:6-60Lens (Diffuser):ClearDimming:Phase-CutFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:L80B10: 100 000h
CRI / Ra: 90 Lumen LED (tc=25): 1850lm Beam Angle: 6-60 Lens (Diffuser): Clear Dimming: Phase-Cut Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: LageB10: 100 000h
Lumen LED (tc=25):1850ImBeam Angle:6-60Lens (Diffuser):ClearDimming:Phase-CutFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:Laose 100 000hLifetime [h]:L80B10: 100 000h
Beam Angle:6-60Lens (Diffuser):ClearDimming:Phase-CutFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:LaoB10: 100 000h
Lens (Diffuser):ClearDimming:Phase-CutFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:TrackLifetime [h]:L80B10: 100 000h
Dimming:Phase-CutFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:TrackLifetime [h]:L80B10: 100 000h
Flickerfree:YesSystem Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:TrackLifetime [h]:L80B10: 100 000h
System Voltage [V]:230V 50HzConnection:Track 3-CircuitMounting:TrackLifetime [h]:L80B10: 100 000h
Connection:Track 3-CircuitMounting:TrackLifetime [h]:L80B10: 100 000h
Mounting:TrackLifetime [h]:L80B10: 100 000h
Lifetime [h]: L80B10: 100 000h
MacAdam (SDCM): 3
Color: Black
Length [mm]: 158mm
Diameter [mm]: 85mm
Weight [kg]: 1kg