





FDV SPEC SHEET

Linea Market

Art. no: 19208-04-2



Linea Market



Art. no: 19208-04-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2972
Lumen LED (tc=25):	4400
Beam Angle:	88
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	5
Lens (Diffuser):	Louvre
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	QuickConnect
-------------	--------------

ELECTRICAL DATA

Dimming:	None
System Power [W]:	35
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	35
Max load pr circuit - B16:	55
Max load pr circuit - C10:	40
Max load pr circuit - C16:	60
Inrush current I _{max} [A]:	5
Inrush current time [μs]:	37
Current Output [mA]:	116



FDV SPEC SHEET

Linea Market

Art. no: 19208-04-2



PRODUCT

Ingress Protection:	IP20
Operating Temperature [°C]:	-
Lifetime [h]:	L80B50: 48 000
Color:	Black
Length [mm]:	1180
Height [mm]:	90
Width [mm]:	60
Weight [kg]:	3,5