




Acrux Adjustable



1 82-88mm






CE . IP54 230V 50Hz IK06	
-----------------------------	--

SPECIFICATIONS

System Power [W]:10WCCT (Color Temperature):2700KCRI / Ra:90Lumen Output:650lmLumen LED (tc=25):650lmBeam Angle:36°Lens (Diffuser):ClearDimming:90System Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:682-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Lightsource Type:	LED (built in)
CRI / Ra:90Lumen Output:650ImLumen LED (tc=25):650ImBeam Angle:36°Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:882-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	System Power [W]:	10W
Lumen Output:650 lmLumen LED (tc=25):650 lmBeam Angle:36°Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:882-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	CCT (Color Temperature):	2700К
Lumen LED (tc=25):650 lmBeam Angle:36°Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	CRI / Ra:	90
Beam Angle:36°Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Lumen Output:	650lm
Lens (Diffuser):ClearDimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Lumen LED (tc=25):	650lm
Dimming:Phase-CutSystem Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Beam Angle:	36°
System Voltage [V]:230V 50HzConnection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Lens (Diffuser):	Clear
Connection:QuickConnectMounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Dimming:	Phase-Cut
Mounting:Recessed, CeilingCut-out [mm]:Ø82-Ø88mmLifetime [h]:L80B10: 100 000hLumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	System Voltage [V]:	230V 50Hz
Cut-out [mm]: Ø82-Ø88mm Lifetime [h]: L80B10: 100 000h Lumen/W: 61lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 55mm Width [mm]: 95mm	Connection:	QuickConnect
Lifetime [h]: L80B10: 100 000h Lumen/W: 61lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 55mm Width [mm]: 95mm	Mounting:	Recessed, Ceiling
Lumen/W:61lm/WMacAdam (SDCM):3Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Cut-out [mm]:	Ø82-Ø88mm
MacAdam (SDCM): 3 Color: White Height [mm]: 55mm Width [mm]: 95mm	Lifetime [h]:	L80B10: 100 000h
Color:WhiteHeight [mm]:55mmWidth [mm]:95mm	Lumen/W:	61lm/W
Height [mm]: 55mm Width [mm]: 95mm	MacAdam (SDCM):	3
Width [mm]: 95mm	Color:	White
	Height [mm]:	55mm
To be recessed in insulation:	Width [mm]:	95mm
	To be recessed in insulation:	No



Adjustable downligth with IP54 classification. Low glare and secluded light source and with modern reflector. Suitable for all rooms included bathroom. Complete with dimmable driver and quick connect for easy installation.