



FDV SPEC SHEET

Exilis II dim

Art. no: 2605-2-01-3



Lighting Solutions



Exilis II dim



Art. no: 2605-2-01-3



FDV SPEC SHEET

Exilis II dim

Art. no: 2605-2-01-3



Lighting Solutions

LIGHT TECHNICAL

| | |
|--------------------------------------|---------------------------|
| Lumen LED (tc=25): | 550 |
| Beam Angle: | 120° |
| CCT (Color Temperature): | 4000 |
| CRI / Ra: | 80 |
| Color Code: | 840 |
| Lens (Diffuser): | Opal |
| Dimming: | Phase-Cut |
| Dimming Phasecut Type: | Leading edge |
| System Power [W]: | 5 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 32 |
| Max load pr circuit - B16: | 52 |
| Max load pr circuit - C10: | 32 |
| Max load pr circuit - C16: | 52 |
| Leakage current [mA]: | 5 |
| Inrush current I _{max} [A]: | 0,31 |
| Socket / Cap-Base: | N/A |
| Connection: | Exilis II 3-pin Connector |
| Ingress Protection: | IP20 |
| Operating Temperature [°C]: | -20 - 40 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | White |
| Length [mm]: | 295 |
| Height [mm]: | 30 |
| Width [mm]: | 22 |