



## PRODUCT SHEET

Ledstripekampanje On/Off 1

Art. no: 102930-01



Lighting Solutions

# Ledstripekampanje On/Off 1



About the product: Discover the impressive LED strip that offers you a dazzling blend of light quality and energy efficiency. With a luminous CCT (Color Temperature) of 2700K, this strip creates a warm and inviting atmosphere perfect for any room in your home. Featuring an impressive CRI (Color Rendering Index) of 90, this LED strip reveals true colors with remarkable accuracy, ensuring your surroundings are showcased in their best light. With a luminous output of 1520 lm/m and an efficiency of 79 lm/W, this LED strip delivers impressive brightness while maintaining energy-efficient operation. The precise MacAdam (SDCM) level of 3 ensures consistent color rendition and a uniform lighting experience without visible color deviations. The wide beam angle of 120 degrees and the impressive density of LEDs with 240 per meter ensure even and consistent illumination across the entire area. With a system voltage of 24VDC and a system power of 19.2 W/m, this LED strip is optimized for reliable performance and long life. Applications: This LED strip is ideal for a variety of applications where accent lighting is needed to create ambiance and functionality. Install it discreetly in closets to provide better visibility and aesthetic appeal to storage areas. Place it along shelves to highlight decorative items or enhance the visibility of books and collections. On stairs, it provides safer conditions and a sophisticated style. Mount it on walls to add depth and interest to the room. With this LED strip, the possibilities to enhance your home and add a touch of elegance and functionality are virtually endless. Package includes: 1 LED strip of 5 meters and 1 on/off driver



### SPECIFICATIONS

CCT (Color Temperature):	2700K
CRI / Ra:	90
Color Code:	927
Lumen Output [lm/ m]:	1520lm/m
Efficiency [lm/ W]:	79lm/w
MacAdam (SDCM):	3
Beam Angle:	120
LED pr. meter:	240
System Voltage [V]:	24VDC
System Power [W/m]:	19,2
Dimming:	Depending on Driver
Mounting:	Adhesive tape
Heat sink needed:	No
Connection:	Cable 2m
Cuttable [mm]:	25mm
Max. length [m]:	5m
Ingress Protection:	IP20
Length:	5000mm
Width:	8mm
Weight:	0,15kg