





Orion G2 Base







| SPECIFICATIONS | |
|---------------------------|--------------------|
| Lightsource Type: | LED (replaceable) |
| System Power [W]: | 35/30/24/19W |
| CCT (Color Temperature): | 4000K |
| CRI / Ra: | 80 |
| Lumen Output: | 5250lm |
| Lumen LED (tc=25): | 5800lm |
| Beam Angle: | 120° |
| Lens (Diffuser): | Frosted |
| Dimming: | Emergency |
| Flickerfree: | Yes |
| System Voltage [V]: | 230V 50Hz |
| Connection: | QuickConnect |
| Mounting: | Surface, Suspended |
| Lifetime [h]: | L80B10: 100 000h |
| Lumen/W: | 150lm/W |
| MacAdam (SDCM): | 3 |
| Through-wiring (mm2): | 5x2,5 |
| Color: | Grey |
| Length [mm]: | 1225mm |
| Height [mm]: | 60mm |
| Width [mm]: | 65mm |
| Weight [kg]: | 1,22kg |
| Emergency light [h]: | 3 hours |
| Emergency light testing: | Selftest |
| Emergency lumen out [lm]: | 350lm |



Orion is an energy-efficient industrial luminaire. With IP65 and IK08, it is suitable for use in tough environments both indoors and outdoors, in wet and dusty surroundings. The luminaire is equipped with a power switch where you can easily change the output via a DIP switch. Through-wiring for series installation and QuickConnect for easy installation. This product is also available with a microwave sensor with wireless communication between luminaires, using the Norlux Wireless Connect system for control.