






FDV SPEC SHEET

Dalim Up&Down 2400lm 40° 2x20W Dark Grey Phasecut
Art. no: 2430-40-7



Lighting Solutions



Dalim Up&Down 2400lm 40° 2x20W Dark Grey Phasec



Art. no: 2430-40-7

LIGHT TECHNICAL	
Lightsource Type:	LED (built in)
Lumen LED (tc=25):	2400
Beam Angle:	40°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Clear

ELECTRICAL DATA	
Dimming:	Phase-Cut
System Power [W]:	2x20
System Voltage [V]:	230V 50Hz
Protection Class:	1
Socket / Cap-Base:	N/A

MOUNTING / CONNECTION	
Connection:	QuickConnect
Mounting:	Surface, Wall



FDV SPEC SHEET

Dalim Up&Down 2400lm 40° 2x20W Dark Grey Phasecut
Art. no: 2430-40-7



Lighting Solutions

PRODUCT

Ingress Protection:	IP65
Impact Protection:	IK08
Operating Temperature [°C]:	-20 - 50
Color:	Dark Grey
RAL:	RAL7024
Length [mm]:	177
Height [mm]:	300
Width [mm]:	140
Weight [kg]:	3,4