



FDV SPEC SHEET

Rigil 900lm 830 360° 15W Quickconnect Dark Grey
Art. no: 2475-36-7



Rigil 900lm 830 360° 15W Quickconnect Dark Grey



Art. no: 2475-36-7

LIGHT TECHNICAL	
Lumen Output:	780
Lumen LED (tc=25):	900
Beam Angle:	360
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Clear
MOUNTING / CONNECTION	
Connection:	QuickConnect
Mounting:	Ground, Bollard

ELECTRICAL DATA	
Dimming:	None
System Power [W]:	15
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	17
Max load pr circuit - B16:	26
Max load pr circuit - C10:	29
Max load pr circuit - C16:	47
Leakage current [mA]:	0,5
Inrush current I _{max} [A]:	15
Inrush current time [μs]:	125
Socket / Cap-Base:	N/A
Current Output [mA]:	250
Voltage Forward Min [V]:	45
Voltage Forward Max [V]:	50



FDV SPEC SHEET

Rigil 900lm 830 360° 15W Quickconnect Dark Grey
Art. no: 2475-36-7



PRODUCT	
Ingress Protection:	IP54
Impact Protection:	IK10
Operating Temperature [°C]:	-20 - 30
Lifetime [h]:	50 000
Color:	Antracite
RAL:	RAL7024
Height [mm]:	800
Width [mm]:	120
Weight [kg]:	2,4
Housing Material :	Aluminium