




FDV SPEC SHEET

Tania Mini 3-Circuit
Art. no: 3551-3-36-22



Lighting Solutions



Tania Mini 3-Circuit



Art. no: 3551-3-36-22

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1050
Lumen LED (tc=25):	1450
Beam Angle:	36°
CCT (Color Temperature):	2700
CRI / Ra:	90
Color Code:	927
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Track, Ceiling

ELECTRICAL DATA

Dimming:	Phase-Cut
Flickerfree:	Yes
System Power [W]:	14,5
System Voltage [V]:	230V 50Hz
Protection Class:	1
Current Output [mA]:	350



FDV SPEC SHEET

Tania Mini 3-Circuit
Art. no: 3551-3-36-22



PRODUCT	
Ingress Protection:	IP20
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Brushed Titan.
Length [mm]:	147
Diameter [mm]:	60
Housing Material :	Aluminium
Housing Material :	Aluminium