



## FDV SPEC SHEET

Eta

Art. no: 688-02-5



*Lighting Solutions*



## Eta



Art. no: 688-02-5

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1117
Lumen LED (tc=25):	1800
Beam Angle:	110
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
Lens (Diffuser):	Opal
UGR (<=):	21

### MOUNTING / CONNECTION

Connection:	Terminal
Mounting:	Surface, Wall, Ceiling

### ELECTRICAL DATA

Dimming:	Sensor (MW)
System Power [W]:	13
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	31
Max load pr circuit - B16:	50
Max load pr circuit - C10:	52
Max load pr circuit - C16:	85
Inrush current I <sub>max</sub> [A]:	5
Inrush current time [μs]:	50
Current Output [mA]:	500



## FDV SPEC SHEET

Eta

Art. no: 688-02-5



*Lighting Solutions*

### PRODUCT

Ingress Protection:	IP65
Impact Protection:	IK08
Corrosion Class:	C3
Lifetime [h]:	L80B10: 100 000
Height [mm]:	130
Width [mm]:	360
Weight [kg]:	2,5