




PRODUCT FAMILY SHEET

(Copy) Universal G2 IP44 Base



(Copy) Universal G2 IP44 Base

Universal is an elegant and splash-proof IP44 LED luminaire designed for interior and industrial use. It features easy installation with pass-through wiring, low glare, and up to 150lm/W efficiency. The luminaire comes with a DIP switch, allowing you to customize the power level as needed, and the Kelvin can be adjusted between 3000K and 4000K. Available in lengths of 600mm, 1200mm, and 1500mm in on/off, sensor (Microwave), or DALI version. This product is also available with a microwave sensor with wireless communication between luminaires, using the Norlux Wireless Connect system for control.

VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
102473-NW-105 -3	47	6800	6110	3000-4000K	105°	Micropris.	80	White	x Wireless C	Quickconnectx2
102472-NW-105 -3	40	5800	5200	3000-4000K	105°	Micropris.	80	White	x Wireless C	Quickconnectx2
102471-NW-105 -3	20	2450	2200	3000	105°	Micropris.	80	White	x Wireless C	Quickconnectx2