



## PRODUCT SHEET

Universal G2 IP44

Art. no: 102471-105-3-ddd



*Lighting Solutions*

# Universal G2 IP44



Universal is an elegant and splash-proof IP44 LED luminaire designed for interior and industrial use. It features easy installation with pass-through wiring, low glare, and up to 150lm/W efficiency. The luminaire comes with a DIP switch, allowing you to customize the power level as needed, and the Kelvin can be adjusted between 3000K and 4000K. Available in lengths of 600mm, 1200mm, and 1500mm in on/off, sensor (Microwave), or DALI version. This product is also available with a microwave sensor with wireless communication between luminaires, using the Norlux Wireless Connect system for control.



### SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	20W
CCT (Color Temperature):	3000-4000K
CRI / Ra:	80
Lumen Output:	2750lm
Beam Angle:	105°
Lens (Diffuser):	Micropris.
Dimming:	DALI2
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	Quickconnectx2
Mounting:	Surface, Ceiling
Lifetime [h]:	L80B10: 100 000h
Lumen/W:	133lm/W
UGR (<=):	24
MacAdam (SDCM):	3
Through-wiring (mm2):	5x2,5
Color:	White
Height [mm]:	52mm
Width [mm]:	155mm