



FDV SPEC SHEET

Iota

Art. no: 3595-03-120-2



Lighting Solutions



Iota



Art. no: 3595-03-120-2

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 40821 |
| Lumen LED (tc=25): | 40000 |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 70 |
| Color Code: | 730 |
| Lens (Diffuser): | Clear |

MOUNTING / CONNECTION

| | |
|-------------|----------|
| Connection: | Cable 1m |
| Mounting: | Wall |

ELECTRICAL DATA

| | |
|---------------------|-----------|
| Dimming: | None |
| System Power [W]: | 300 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Socket / Cap-Base: | N/A |



FDV SPEC SHEET

Iota

Art. no: 3595-03-120-2



Lighting Solutions

PRODUCT

| | |
|------------------------------|--------------------------|
| Ingress Protection: | IP65 |
| Impact Protection: | IK08 |
| Corrosion Class: | C3 |
| Wind force (EPA) [m2] at 0°: | 0,24 |
| Surge Protection: | L-N = 6KV, L/N-PE = 10KV |
| Operating Temperature [°C]: | -30 - 50 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | Black |
| Length [mm]: | 567 |
| Height [mm]: | 465 |
| Width [mm]: | 97 |
| Weight [kg]: | 9,5 |
| Housing Material : | Aluminium |
| Diffuser Material: | Polycarbonate |