



PRODUCT SHEET

Driver On/Off 1500mA max 60W 20-40V 18i3 Male/ EPN0034

Art. no: 0300-20



Driver On/Off 1500mA max 60W 20-40V 18i3 Male/ EP

Tridonic driver preset at 1500mA, max 60W.

Primary side 0,3m cable with 18i3 (male).

Secondary side EPN0034 (female).



SPECIFICATIONS

| | |
|--------------------------------------|---|
| System Power [W]: | 60W |
| Dimming: | None |
| CC or CV: | CC |
| CC [mA]: | 900 - 1750mA |
| CC (forward voltage driver) [V]: | 20 - V |
| Max output voltage [V]: | 60 |
| Output Current Tolerance [%]: | 5% |
| Current Ripple [%]: | 5% |
| Current setting: | I-Select 2 Plug (Tridonic), Ready2Mains |
| Expected Lifetime: | 100000h |
| System Voltage [V]: | 230V 50Hz V |
| Protection Class: | 1 or 2 |
| Leakage current [mA]: | 0,25mA |
| Inrush current I _{max} [A]: | 25,9A |
| Inrush current time [μs]: | 252μs |
| Manufacture: | Tridonic |
| Manufacture P/N: | 28000702 - Driver LC 60W 9001750mA flex |
| Primary Connection: | 18i3 male |
| Secondary Connection: | EPN0034 female |