



PRODUCT SHEET

Driver On/Off 600mA max 31W 23-42V 18i3 Male/ EPN0034

Art. no: 0300-40



Driver On/Off 600mA max 31W 23-42V 18i3 Male/ EPN



SPECIFICATIONS

| | |
|--------------------------------------|----------------|
| System Power [W]: | 30W |
| Dimming: | None |
| Flicker metric (Pst LM) <: | 1 |
| Stroboscopic effect metric (SVM) <: | 0,4 |
| CC or CV: | CC |
| CC [mA]: | 500 - 700mA |
| CC (forward voltage driver) [V]: | 23 - 42V |
| Max output voltage [V]: | 60 |
| Current Ripple [%]: | 5% |
| Expected Lifetime: | 50000h |
| System Voltage [V]: | 230V 50Hz V |
| Protection Class: | 2 |
| Max load pr circuit - B10: | 27 |
| Max load pr circuit - B16: | 44 |
| Max load pr circuit - C10: | 41 |
| Max load pr circuit - C16: | 66 |
| Inrush current I _{max} [A]: | 5A |
| Inrush current time [μs]: | 70μs |
| Manufacture: | Osram |
| Primary Connection: | 18i3 male |
| Secondary Connection: | EPN0034 female |
| Length: | 145mm |
| Height: | 29,5mm |
| Width: | 43mm |
| Weight: | 0,09kg |