



C Line NWC






8 Bluetooth





| SPECIFICATIONS |
|----------------|
|----------------|

| Si Lenieritonio | |
|--------------------------|-------------------------|
| Lightsource Type: | LED (replaceable) |
| System Power [W]: | 80W |
| CCT (Color Temperature): | 4000K |
| CRI / Ra: | 80 |
| Lumen Output: | 13600lm |
| Lumen LED (tc=25): | 15800lm |
| Beam Angle: | 90° |
| Lens (Diffuser): | Clear |
| Dimming: | Norlux Wireless Connect |
| Flickerfree: | Yes |
| System Voltage [V]: | 230V 50Hz |
| Connection: | Quickconnectx2 |
| Mounting: | Surface, Ceiling |
| Lifetime [h]: | L80: 100 000h |
| Lumen/W: | 170lm/W |
| MacAdam (SDCM): | 3 |
| Color: | Steel |
| Length [mm]: | 1550mm |
| Height [mm]: | 50mm |
| Width [mm]: | 76mm |
| Weight [kg]: | 2,54kg |
| | |



C Line NWC is an industrial light fixture for ceiling mounting, with input for mounting Norlux Wireless Connect sensor or node. With Norlux Wireless Connect integrated into the luminaire, you have modern lighting control technology without the need for extra cabling. This opens up opportunities for control, dimming, individual grouping, and sensor integration completely wirelessly with Bluetooth communication. Simple programming via smartphone (iOS or Android). The luminaire has many applications such as industrial and warehouse use. Download the app here: <u>Norlux Wireless Connect_iOS</u> <u>Norlux Wireless Connect_Android</u>