




FDV SPEC SHEET

Halo Pendant Dimmable
Art. no: 1127-2-120-2



Halo Pendant Dimmable



Art. no: 1127-2-120-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1400
Lumen LED (tc=25):	3200
Beam Angle:	120
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	6
Lens (Diffuser):	Frosted
UGR (<=):	16

MOUNTING / CONNECTION

Connection:	18i3 Quick connection
Mounting:	Ceiling, Pendant

ELECTRICAL DATA

Dimming:	Phase-Cut
Dimming Output Type:	Amplitude Modulation
Dimming Phasecut Type:	Leading / Trailing edge
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	28
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	52
Max load pr circuit - B16:	84
Max load pr circuit - C10:	52
Max load pr circuit - C16:	84
Leakage current [mA]:	7
Inrush current I _{max} [A]:	5
Inrush current time [μs]:	100
Voltage Forward Min [V]:	2,6
Voltage Forward Max [V]:	3,4



FDV SPEC SHEET

Halo Pendant Dimmable
Art. no: 1127-2-120-2



PRODUCT	
Ingress Protection:	IP20
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 50.000
Color:	Black
Length [mm]:	800
Height [mm]:	34
Width [mm]:	800
Weight [kg]:	3