



## FDV SPEC SHEET

Zoom Mini Spotlight

Art. no: 7063-02-560-3-ddd



Lighting Solutions



# Zoom Mini Spotlight



Art. no: 7063-02-560-3-ddd

### LIGHT TECHNICAL

|                          |                |
|--------------------------|----------------|
| Lightsource Type:        | LED (built in) |
| Lumen LED (tc=25):       | 1250           |
| Beam Angle:              | 5°-60°         |
| CCT (Color Temperature): | 2700           |
| CRI / Ra:                | 90             |
| Color Code:              | 927            |
| MacAdam (SDCM):          | 3              |
| Lens (Diffuser):         | Clear          |

### MOUNTING / CONNECTION

|             |                 |
|-------------|-----------------|
| Connection: | Track 3-Circuit |
| Mounting:   | Track, Ceiling  |

### PRODUCT

|                     |                 |
|---------------------|-----------------|
| Ingress Protection: | IP20            |
| Lifetime [h]:       | L80B10: 100 000 |
| Color:              | White           |
| Length [mm]:        | 261             |
| Width [mm]:         | 60              |
| Weight [kg]:        | 0,95            |

### ELECTRICAL DATA

|                                      |                      |
|--------------------------------------|----------------------|
| Dimming:                             | DALI2                |
| Flicker metric (Pst LM) <:           | 1                    |
| Stroboscopic effect metric (SVM) <   | 0,4                  |
| System Power [W]:                    | 15                   |
| System Voltage [V]:                  | 230V 50Hz            |
| Dimming Output Type:                 | Amplitude Modulation |
| Protection Class:                    | 1                    |
| Max load pr circuit - B10:           | 25                   |
| Max load pr circuit - B16:           | 40                   |
| Max load pr circuit - C10:           | 37                   |
| Max load pr circuit - C16:           | 60                   |
| Leakage current [mA]:                | 0,7                  |
| Inrush current I <sub>max</sub> [A]: | 30                   |
| Inrush current time [μs]:            | 100                  |
| Current Output [mA]:                 | 500                  |
| Voltage Forward Min [V]:             | 34,2                 |
| Voltage Forward Max [V]:             | 37,7                 |